

## Teknik bilgiler model TTS

Model	EAN-No. 4025092*	Kapasite kg	Çalışma genişliği Z mm	Kanca ağızı mm	Ağırlık kg
TTS 1,0/1500	*552646	1.000	700 - 1.500	18	40
TTS 2,0/1500	*552295	2.000	700 - 1.500	18	41
TTS 3,0/1500	*553988	3.000	700 - 1.500	21	53
TTS 5,0/1500	*551281	5.000	700 - 1.500	23	79
TTS 7,5/1500	*553995	7.500	700 - 1.500	32	98
TTS 10,0/1500	*552219	10.000	700 - 1.500	32	117
TTS 12,5/1500	*554008	12.500	700 - 1.500	40	116
TTS 15,0/1500	*554015	15.000	700 - 1.500	40	137
TTS 20,0/1500	*554022	20.000	700 - 1.500	50	180
TTS 25,0/1500	*554039	25.000	700 - 1.500	50	226
TTS 1,0/2500	*554046	1.000	1.500 - 2.500	18	58
TTS 2,0/2500	*552158	2.000	1.500 - 2.500	18	84
TTS 3,0/2500	*552448	3.000	1.500 - 2.500	21	105
TTS 5,0/2500	*552424	5.000	1.500 - 2.500	23	127
TTS 7,5/2500	*554053	7.500	1.500 - 2.500	32	178
TTS 10,0/2500	*554060	10.000	1.500 - 2.500	32	215
TTS 12,5/2500	*554077	12.500	1.500 - 2.500	40	198
TTS 15,0/2500	*554084	15.000	1.500 - 2.500	40	237
TTS 20,0/2500	*554091	20.000	1.500 - 2.500	50	287
TTS 25,0/2500	*554107	25.000	1.500 - 2.500	50	342
TTS 1,0/3500	*552684	1.000	1.700 - 3.500	18	95
TTS 2,0/3500	*554114	2.000	1.700 - 3.500	18	137
TTS 3,0/3500	*554121	3.000	1.700 - 3.500	21	162
TTS 5,0/3500	*554138	5.000	1.700 - 3.500	23	228
TTS 7,5/3500	*554145	7.500	1.700 - 3.500	32	278
TTS 10,0/3500	*554152	10.000	1.700 - 3.500	32	317
TTS 12,5/3500	*554169	12.500	1.700 - 3.500	40	295
TTS 15,0/3500	*551403	15.000	1.700 - 3.500	40	340
TTS 20,0/3500	*554176	20.000	1.700 - 3.500	50	451
TTS 25,0/3500	*554183	25.000	1.700 - 3.500	50	512
TTS 1,0/5000	*554367	1.000	2.000 - 5.000	18	190
TTS 2,0/5000	*554374	2.000	2.000 - 5.000	18	219
TTS 3,0/5000	*554381	3.000	2.000 - 5.000	21	260
TTS 5,0/5000	*554398	5.000	2.000 - 5.000	23	372
TTS 7,5/5000	*554404	7.500	2.000 - 5.000	32	423
TTS 10,0/5000	*554411	10.000	2.000 - 5.000	32	531
TTS 12,5/5000	*554428	12.500	2.000 - 5.000	40	449
TTS 15,0/5000	*554435	15.000	2.000 - 5.000	40	568
TTS 20,0/5000	*554442	20.000	2.000 - 5.000	50	691
TTS 1,0/8000	*554459	1.000	3.000 - 8.000	18	342
TTS 2,0/8000	*554466	2.000	3.000 - 8.000	18	458
TTS 3,0/8000	*554473	3.000	3.000 - 8.000	21	547
TTS 5,0/8000	*554480	5.000	3.000 - 8.000	23	788
TTS 7,5/8000	*554497	7.500	3.000 - 8.000	32	883
TTS 10,0/8000	*554503	10.000	3.000 - 8.000	32	1.319
TTS 12,5/8000	*554510	12.500	3.000 - 8.000	40	979
TTS 15,0/8000	*554527	15.000	3.000 - 8.000	40	1.046

## Boyutlar model TTS

Model	TTS 1,0/1500	TTS 2,0/1500	TTS 3,0/1500	TTS 5,0/1500	TTS 7,5/1500	TTS 10,0/1500	TTS 12,5/1500	TTS 15,0/1500	TTS 20,0/1500	TTS 25,0/1500
B, mm	410	440	540	625	710	805	835	880	990	1.200
C, mm	110	135	160	180	200	260	260	260	260	300
D, mm	25	30	35	40	60	70	75	85	90	100
E, mm	60	75	90	100	130	130	140	140	160	160

Model	TTS 1,0/2500	TTS 2,0/2500	TTS 3,0/2500	TTS 5,0/2500	TTS 7,5/2500	TTS 10,0/2500	TTS 12,5/2500	TTS 15,0/2500	TTS 20,0/2500	TTS 25,0/2500
B, mm	410	475	580	645	755	850	885	925	1.030	1.225
C, mm	110	135	160	180	200	260	260	260	260	300
D, mm	25	30	35	40	60	70	75	85	90	100
E, mm	60	75	90	100	130	130	140	140	160	160

Model	TTS 1,0/3500	TTS 2,0/3500	TTS 3,0/3500	TTS 5,0/3500	TTS 7,5/3500	TTS 10,0/3500	TTS 12,5/3500	TTS 15,0/3500	TTS 20,0/3500	TTS 25,0/3500
B, mm	410	500	605	685	780	875	905	950	1.085	1.270
C, mm	110	135	160	180	200	260	260	260	260	300
D, mm	25	30	35	40	60	70	75	85	90	100
E, mm	60	75	90	100	130	130	140	140	160	160

Model	TTS 1,0/5000	TTS 2,0/5000	TTS 3,0/5000	TTS 5,0/5000	TTS 7,5/5000	TTS 10,0/5000	TTS 12,5/5000	TTS 15,0/5000	TTS 20,0/5000
B, mm	465	520	625	710	800	920	950	995	1.125
C, mm	110	135	160	180	200	260	260	260	260
D, mm	25	30	35	40	60	70	75	85	90
E, mm	60	75	90	100	130	130	140	140	160

Model	TTS 1,0/8000	TTS 2,0/8000	TTS 3,0/8000	TTS 5,0/8000	TTS 7,5/8000	TTS 10,0/8000	TTS 12,5/8000	TTS 15,0/8000
B, mm	485	560	670	755	865	980	1.015	1.055
C, mm	110	135	160	180	200	260	260	260
D, mm	25	30	35	40	60	70	75	85
E, mm	60	75	90	100	130	130	140	140

